Shenzhen SMX Display Technology Co., Ltd

www.smxprojector.com

Add: 611, Block A, Zhihui Innovation Center, Hangcheng Industrial, Xixiang St., Baoan Dist., Shenzhen

Contact: May Wei Email: may@smxdisplay.com Wechat/Whatsapp: 0086 18923801593

Specification of 3500 Lumen 3LCD Projector		
Model		
	Model No.	MX-351XS
	Resolution	XGA
	ID. Photo	
Brightness		
	Brightness (Ansi Lumens)	3500
Overall Spec		
Panel	Display Panel	3x0.63”
	Display Technology	Liquid Crystal Display
	Native Resolution	XGA (1024x768)
Projection Lens	Zoom/Focus	Manual
	Throw Ratio	60"@1.8m；1.47~1.77：1
	F	F:2.1~2.25
	f	f=19.109~22.936mm
	Zoom Ratio	1.2x optics
	Screen size	0.887~10.899m（30"~300"）
Contrast	Contrast Ratio(Min)	15000:1 (w/o IRIS)
Noise	Noise(dB)@1m	ECO: 35dB Normal: 38dB
Uniformity	Uniformity(Actual Min) -JISX6911	80%
AR	Aspect Ratio	4:3 (Standard)/16:9(Compatible)
Terminal(I/O port)		
Input	HDMI	*2
	USB-A	*1
Control	RS232	*1
General Spec		
Audio	Speaker	N/A
Power Consumption	Power Requeirements	100~240V@ 50/60Hz
	Power consumption(W)	300
	Power Consumption(ECO)	250
	ECO Standby Mode Power Consumption	<0.5W

Cooling Set Up	Operating Temp.	5℃~40℃(35~ ECO)
	Store Temp.	-10℃~~50℃
	Oparating Humidity	20%~80%
	High altitude	0 to 3000 m
Other Functions		
Keystone	Keystone Correction	V: ±30°/ H: ±30° 4 corner (Manual)
OSD	Languages	9 languages: English / Chinese / French / Spanish/ Portuguese / Korean/ Russian /Vietnamese/Arabic
Scanning Frequency	H-Synch Range	15~100KHz
	V-Synch Range	48~85Hz
Display Resolution	Computer Signal Input	VGA, SVGA, XGA, SXGA,WXGA,UXGA,WUXGA,Mac
SW setting	Auto Setup	INPUT SEARCH
	Suspend	No signal to Poweroff
	Picture mode	Dynamic、Standard、Cinema、 Blackboard、Colorboard
	Lamp mode	NORMAL,ECO
	Filter Cleaning Cycle	200/500/1000 hours
	Cooling time	0S,60s
	D-Zoom	300%
	Others	Customizable multi-function keys
Dimension&Weight		
	MAX Dimensions (WxHxD mm)	345*261*99
	Net. Weight (KG)	~3.1
	Packaging Size (WxHxD mm)	442*368*195
	Gross. Weight (KG)	4.5
Accessory		
	Standard Accessaries	Power cord, HDMI cable,Remote control